



KEY FEATURES

Real-time H-Star technology for decimeter or subfoot accuracy in the field

OmniSTAR HP, XP, or VBS technology for worldwide decimeter to submeter accuracy in the field

Optional support for GLONASS

Rugged receiver able to work in extreme temperatures with an internal all day battery

Choice of field device, field software, and setup style to suit your requirements



FLEXIBLE GNSS RECEIVER WITH REAL-TIME DECIMETER ACCURACY

Whether you need to relocate buried pipes and cables, or accurately map underground assets and critical infrastructure, the Trimble® GPS Pathfinder® ProXRT receiver has it all. This real-time decimeter receiver adds another dimension to your field kit, giving you the confidence to know the job was done right while you're still on site. Combining H-Star™ technology, OmniSTAR support, and with the option of GLONASS support on top of dual-frequency GNSS, the GPS Pathfinder ProXRT receiver is a truly versatile solution offering you the accuracy you need, worldwide.

Decimeter accuracy with real-time H-Star

You need accuracy and you want it now. The GPS Pathfinder ProXRT receiver brings Trimble H-Star technology to the field in real time; just connect to a Trimble VRS™ network or a local base station correction source and you can collect decimeter (10 cm / 4 inch) or subfoot (<30 cm) positions in the field. Simply use a wireless link to your local VRS™ network, or set up your own base station for the flexibility to work wherever you need to.

Decimeter accuracy in real time with

OmniSTAR HP

If a VRS network or a local base station is not available in your area, then real-time decimeter accuracy with OmniSTAR HP couldn't be easier. The OmniSTAR antenna is integrated so there's no need to carry any extra equipment—just purchase a subscription and wait for the over the air corrections. The Trimble GPS Pathfinder ProXRT receiver is also capable of using the OmniSTAR XP service (for 20 cm accuracy) and OmniSTAR VBS service (for instantaneous submeter accuracy).

Optional GLONASS support

Installing the GLONASS option on your GPS Pathfinder ProXRT receiver increases the number of GNSS satellites that you observe when working in the field. GLONASS improves your ability to maintain lock on enough satellites to keep working when sky visibility becomes limited, letting you work for longer in tough environments. Tracking GLONASS satellites as well as GPS satellites can also improve productivity by reducing the time required to achieve real-time or postprocessed decimeter accuracy. G2, an optional service to OmniSTAR HP that provides GLONASS corrections, can also be used with the GPS Pathfinder ProXRT receiver with GLONASS option.

Galileo Support

The latest generation of Trimble 360™ receiver technology enables tracking of the Galileo GIOVE-A and GIOVE-B test satellites for signal evaluation and test purposes, through the Web Browser interface available with the NMEA optional upgrade.

Built for the field

The Trimble GPS Pathfinder ProXRT receiver is built for the tough field conditions where you work, and can operate even in extreme temperatures. The integrated lithium-ion battery is designed for all day use, so you can continue working for as long as you need.

The choice is yours

You can choose the field computer and software to suit your workflow. The Trimble GPS Pathfinder ProXRT receiver is ready to use with a variety of field computers, including laptops, Tablet PCs and PDAs, and of course with any Trimble rugged field computer: a Trimble Nomad® G or Juno® series handheld, a Trimble Recon® handheld, or a Trimble Yuma® rugged tablet computer.

Choosing mapping software? The Trimble TerraSync™ software or the Trimble GPScorrect™ extension for Esri ArcPad software provides a complete solution from field to office and back. Or use an application built using the GPS Pathfinder Field Toolkit that's totally customized to your needs.

And the GPS Pathfinder ProXRT receiver gives you the flexibility to choose the style of setup to suit your requirements. Choose a pole for added precision or a backpack for your convenience and added comfort.

Real time. Real accurate. Real choice.

The Trimble GPS Pathfinder ProXRT receiver delivers a winning combination of decimeter accuracy with real-time positioning, truly taking GIS data collection to a new level. No matter where in the world you work, the GPS Pathfinder ProXRT receiver gives you a complete real-time decimeter solution.

TRIMBLE GPS PATHFINDER ProXRT RECEIVER

STANDARD FEATURES

GNSS

- Trimble H-Star technology for decimeter (10 cm / 4 inch) and subfoot (< 30 cm) accuracy in either real time or postprocessed¹
- "Worldwide" support for OmniSTAR HP (decimeter), XP (20 cm), and VBS (submeter) services²
- DGPS corrections by radio link, NTRIP, or VRS network through cell phone
- Integrated SBAS³
- Trimble Everest™ multipath rejection technology

System

- Integrated all day battery
- Integrated Bluetooth® wireless technology for operation on a pole
- Rugged housing

Standard accessories

- Trimble Tornado™ antenna
- Antenna cable
- Power supply with international adaptor kit
- Null modem cable, DB9-Lemo cable, and multiport adaptor
- Hard carry case
- User Guide on CD

OPTIONAL FEATURES

Receiver options

- GLONASS support
- NMEA output

Optional software

- Trimble TerraSync software
- Trimble GPScorrect extension for Esri ArcPad software
- Custom applications built with the Trimble GPS Pathfinder Field Toolkit
- Trimble GPS Pathfinder Office software
- Trimble GPS Analyst™ extension for Esri ArcGIS for Desktop software

Optional field computers

- Field computers powered by the Windows Mobile® version 5.0 software or version 6.x operating system, or Windows Embedded Handheld version 6.x operating system such as:
 - Trimble Juno® series handheld
 - Trimble Nomad G series handheld
 - Trimble Yuma rugged tablet computer
 - Trimble Recon handheld
- Field computer running Windows® desktop operating system

Optional accessories

- Backpack kit (backpack, 1 foot pole segment, quick release adapters)
- Pole kit (2 m carbon fibre range pole, pole mount kit, quick release adapters)
- Magnetic vehicle mount

TECHNICAL SPECIFICATIONS

Physical

GNSS receiver and integrated battery	
Size	24 cm x 12 cm x 5 cm including connectors (9.4 in x 4.7 in x 1.9 in)
Weight	1.55 kg (3.42 lbs)
Battery	13 hours internal Li-Ion battery, rechargeable in unit
Antenna	
Size	16.1 cm diameter x 7.4 cm height (6.1 in x 3 in)
Weight	0.82 kg (1.8 lbs)

Environmental—GNSS receiver

Temperature	-40 °C to +65 °C (-40 °F to +149 °F)
Humidity	MIL-STD 810F, Method 507.4
Waterproof	IP67 for submersion to depth of 1 m (3.28 ft), dustproof
Shock and Vibration	Designed to survive a 1 m (3.28 ft) pole drop onto a hard surface
Shock, operating	To 40 g, 10 ms, saw-tooth
Shock, non-operating	To 75 g, 6 ms
Vibration	Tested to Trimble ATV profile (4.5 gRMS)

Environmental—antenna

Temperature	-40 °C to +70 °C (-4 °F to +158 °F)
Humidity	100% humidity proof, fully sealed
Shock	MIL-STD-810-F to survive a 2 m (6.56 ft) drop onto concrete
Vibration	MIL-STD-810-F on each axis

Input/output

Serial	2 Serial ports (DB9 and Lemo)
Bluetooth	Fully-integrated, fully-sealed 2.4 GHz, 3 channel Bluetooth ⁴ module
Interface	Power button and front panel display

Protocols

Data Output	Internal Trimble only (Note: NMEA output optional)
Real-time corrections	RTCM 2.X, CMR, CMR+

GNSS

Channels	220
Satellite systems	GPS, GLONASS ⁵ , Galileo ⁶ , SBAS
GPS	L1C/A, L2C, L2E (Trimble method for tracking L2P)
GLONASS	L1C/A, L1P, L2C/A, L2P
Galileo	GIOVE-A, GIOVE-B
OmniSTAR	VBS, HP (G2) ⁷ , & XP
SBAS	L1C/A supporting WAAS, MSAS & EGNOS

Accuracy (HRMS) after correction⁸

Real-time positioning	
H-Star ¹	
Short baseline (within a VRS network or <30 km)	10 cm
Long baseline (30–80 km)	Subfoot (<30 cm)
OmniSTAR ²	
HP (+G2) ⁷	10 cm
XP	20 cm
VBS	Submeter
Code corrections (SBAS or external correction source)	Submeter ³
Postprocessed positioning	
H-Star postprocessed	10 cm + 1 ppm ⁹
Carrier postprocessed with 45 minutes tracking satellites	1 cm + 2 ppm ¹⁰
Code postprocessed	50 cm + 1 ppm

- 1 Real-time decimeter accuracy can be achieved with H-Star data when the baseline length is less than 30 km. Both the base and the rover must be dual frequency and observing at least five common satellites (six during dual-satellite constellation operation). In less optimal conditions or at ranges between 30 km and 80 km, real-time subfoot accuracy can be achieved. H-Star specified accuracy is typically achieved within 2 minutes.
- 2 OmniSTAR HP/XP typically require up to 60 minutes initialization time to achieve the specified accuracy. Refer to www.OmniSTAR.com for additional information on accuracy specifications and initialization times.
- 3 SBAS (Satellite Based Augmentation System). Includes WAAS (Wide Area Augmentation System) available in North America only, EGNOS (European Geostationary Navigation Overlay System) available in Europe only, and MSAS, available in Japan.
- 4 Bluetooth type approvals are country specific. The GPS Pathfinder ProXRT receiver has Bluetooth approval in the U.S. and EU. For other countries consult your local Distributor.
- 5 The ProXRT receiver can be purchased with GLONASS pre-installed or the ProXRT can be purchased without GLONASS and subsequently upgraded to GLONASS capability if required.
- 6 Model 2 of the GPS Pathfinder ProXRT receiver (shipping from October 2010) includes the latest generation of Trimble 360 receiver technology and is capable of tracking the Galileo GIOVE-A and GIOVE-B test satellites for signal evaluation and test purposes, through the Web Browser interface available with the NMEA optional upgrade. This powerful receiver technology conforms to the current Open Service Signals-in-Space Interface Control Document (OS SIS ICD), Issue 1, Revision 1, September 2010. Sale of receivers based on information in the Galileo ICD is subject to the licensing terms for manufacturers promulgated by the European Commission (EC).
- 7 An optional service to OmniSTAR HP that provides GLONASS corrections, can also be used with the GPS Pathfinder ProXRT receiver with GLONASS option.
- 8 Horizontal Root Mean Squared accuracy. Except in conditions where most GPS signals are affected by trees, or buildings, or other objects. Except when using VRS or OmniSTAR corrections, accuracy varies with proximity to base station by +1 ppm for code postprocessing and real-time.
- 9 The following factors increase the availability of 10 cm accuracy after H-Star postprocessing: longer elapsed time tracking uninterrupted L1/L2 carrier phase data, tracking of more GPS or GLONASS satellites with L2 measurements, shorter distance to the base station(s), and use of more (than one) base stations for postprocessing.
- 10 45 minute carrier capability applies only to the GPS Pathfinder Office software and is limited to 10 km from the base station.

Specifications apply to Model 2 of the ProXRT receiver and are subject to change without notice.

© 2008-2012, Trimble Navigation Limited. All rights reserved. Trimble, the Globe & Triangle, GPS Pathfinder, Juno, Nomad, Recon, and Yuma are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. Everest, GPS Analyst, GPScorrect, H-Star, TerraSync, Tornado, and VRS are trademarks of Trimble Navigation Limited. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Trimble Navigation Limited is under license. Windows and Windows Mobile are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. All other trademarks are the property of their respective owners. PN 022501-1361 (02/12)



Jl. Ciputat Raya No. 4F Kebayoran Lama, Jakarta 12240
 Telp. (021) 723 8381 Fax. (021) 723 8403
 Email. info@gpslands.co.id
 Website. <http://www.gpslands.co.id>

NORTH & SOUTH AMERICA

Trimble Navigation Limited
 10355 Westmoor Drive
 Suite #100
 Westminster, CO 80021
 USA
 +1-720-587-4574 Phone
 +1-720-587-4878 Fax

EUROPE & AFRICA

Trimble Germany GmbH
 Am Prime Parc 11
 65479 Raunheim
 GERMANY
 +49-6142-2100-0 Phone
 +49-6142-2100-550 Fax

ASIA-PACIFIC & MIDDLE EAST

Trimble Navigation
 Singapore PTE Limited
 80 Marine Parade Road
 #22-06 Parkway Parade
 Singapore, 449269
 SINGAPORE
 +65-6348-2212 Phone
 +65-6348-2232 Fax



www.trimble.com
store.trimble.com